



COMPACT CONTROL PANEL, INNOVATIVE PERIPHERALS, EASY
INSTALLATION, RICH MAINTENANCE TOOLS AND SUPERIOR
FLEXIBILITY IN DAILY USE

**The high-performance wireless
residential alarm system**

Domonial Wireless Security

Domonial is a compact, wireless security system for residential installations. Its built-in communicator brings remote maintenance and diagnostics into general use for routine inspections and alarm activations. The optional GSM module can be used as a back up for the PSTN or as the main network connection. A great choice of innovative controlling equipment helps provide a system best-fitted to every user's lifestyle.



Domonial main features

Wireless system with wired extensions: programmable output, XM10 transmitter, remote audio devices and external tamper

- Built-in sounder for intruder and fire alarm
- Built-in PSTN communicator and optional plug-on GSM module for connection to a monitoring centre or nominated number: protocols Secom3, Contact Id, Cesa, Surtec
- Built-in speaker/microphone: listen-in facility and talk initiated by operator or user
- Full set, part set and annex set functions for protection of the entire site or separate areas
- Leading edge radio transmission technology

Peripherals

The Domonial security system is complimented by a comprehensive range of wireless peripherals and additional wired extensions



Sensor range

DO800M*

Door contact

Ultra-small wireless door contact.



(102x22x23mm)

BVA800HF

Glass break detector



(110x85mm)

DFO800M

Smoke sensor

Wireless smoke sensor with 100m² coverage. Dedicated maintenance fault information for chamber cleaning.



(102x45mm)

IRX800GY*

Passive Infrared sensor

Discrete wireless PIR sensor with 10m range.



(70x130x52mm)

IRX802HF

Passive Infrared sensor with look down

Look down dedicated sensor.



(70x130x52mm)

IRPI800M*

Pet immune Passive Infrared sensor

Wireless pet-immune PIR sensor (up to 36kg) with 11m x 12m range.



(112x60x40mm)

IRV800M*

Passive Infrared sensor with camera

Wireless PIR sensor with built-in camera for sequential image capture PIR range up to 10m.



(80x165x70mm)

System

Keypad & Keyfob

TCU2-800M*

LCD Keypad

Keypad with LCD display, TAG prox reader and keypad for PIN entry.

Optional mobile mode for part set:

keypad can be removed from bracket and follow the user inside the home.

Full set/part set/annex set users TAG and/or PIN setup

Event log, system diagnostics, receivers remote control.

Can be used as a programming tool for the installer.



(62x155x28mm)

CSK800HF

Keypad

TAG prox reader and keypad for PIN entry.

Full set/part set/annex set.

Alert function, Receivers control.



(85x135x25mm)

TC805HF

Keyfob

4-button keyfob.

Full set/part set/Alert

function, Receivers control.



(38x88x19mm)



Maintenance Tools & Alarm Receiver

The Domonial alarm system is programmed and maintained using software tools developed for standard platforms:

DOMOPC

Local and remote programming and maintenance on PC

- Windows 2000, XP support, serial connection to the panel using specific cable, remote connection using secured modem Domodem.
- User-friendly interface with online installation guide and saving and reporting facilities.

DOMOPDA

- Local programming tool for PDA
- Palm OS support, serial or USB connection to the panel using specific cable.

- Interactive screens with a rich set of programmable features.
- PDA device can be supplied (PK-U version)



IST Technical Server, PE Alarm Receiver, WAP Portal

- ISDN connection with dynamic channel allocation.
- Audio and image processing for alarm verification.
- Network services for automated installations maintenance.
- WAP portal application.

Contact us for more information

NEW – Panel can be fully programmed with the TCU2-800M LCD Keypad

Other peripherals

SEF800HF

External sounder with flash


Wireless external sounder at 105dB with strobe warning light.



(355x215mm)

GSM Communicator Add-on Module*

Plug-on module for GSM audio, Data and SMS. Can be used as PSTN backup or as main signalling path.



Other peripherals include the **DOD800HF** door contact with wired extension, the **SI800HF**, indoor sounder.

* These peripherals will achieve PD6662 installation compliance

Domonial Panel Specifications

Feature	Specification	Details
Zones / sensors	30	The Domonial panel can register up to 32 peripherals in different sensor, keypad, sounder and receiver configurations
Keypads	4	
Keyfobs	10	
Wireless sirens indoor/outdoor	4	
Receivers: Radio and X10 plugs, IRVideo sensors	12	
Alert functions	3	
Users	Up to 10	The master user sets up other users
Full set, Part set, Annex set	3 protection areas	
Built-in sounder	90 dBA	7 levels and progressive mode
Built-in audio verification	Speaker/microphone	
Event log	1000	
Narrow band FM radio frequency	10 sub-channels in the 868-870 MHz band with anti-jamming technology	
Wired output	1	Programmable
X10 extension	1	Connector to XM10 transmitter
Wired audio modules extension	Up to 3 TP modules	
Built-in PSTN communicator	1	
Optional GSM communicator	1	
System integrity and diagnostics	Tamper protection, adaptive radio jamming detection, monitoring of peripheral radio transmission, power supply and PSTN/GSM availability	

Honeywell reserve the right to alter the specification of products without prior notice

Honeywell Security & Custom Electronics

Newhouse Industrial Estate
Motherwell
Lanarkshire
ML1 5SB
Tel: +44 1698 73 8200
Fax: +44 1698 73 8300
www.honeywell.com/security/uk

Honeywell Security & Custom Electronics

Parc Gutenberg
8, voie La Cardon
91120 Palaiseau
France
Tel: +33 (0) 1 64 53 80 40
Fax: +33 (0) 1 64 53 80 44
www.honeywell.com/security/fr

Honeywell Security & Custom Electronics

C/ Mijancas nº1, 3a planta
Poligono Industrial Las Mercedes
28022 Madrid
España
Tel: +34 902 667 800
Fax: +34 902 932 503
www.honeywell.com/security/es

Honeywell Security Deutschland

Novar GmbH
Johannes-Mauthe-Str. 14
72458 Albstadt
Tel: +49 (0) 7431/ 801- 0
Fax: +49 (0) 7431/ 801 1220
www.honeywell.com/security/de

Honeywell Security & Custom Electronics

Via della Resistenza 53/59,
20090 Buccinasco
Italy
Tel: +39 (0) 245 717 91
Fax: +39 (0) 245 701 034
www.honeywell.com/security/it

Honeywell Security & Custom Electronics

Network 121
1446 WV Purmerend
The Netherlands
Tel: +31 (0) 299 410200
Fax: +31 (0) 299 410201
www.honeywell.com/security/nl

To reorder this literature,
call +44 (0)870 240 3387 quoting ref:
HSCE-DOMONIALUK-03-EN(1106)SB-C
November 2006
© 2006 Honeywell International Inc.